

Jiangsu Weijie Automation Equipment Co., Ltd.

Automatic wrapping film packing machine/wrapper

Focus on packaging solutions

Smart; efficient; safe



CONTENTS

- 01 Company Introduction
- 02 Core product
- 03 Customer use case

Part 1 Company Introduction



Business scope

Pts such as winding machines, strapping machines, belt threading machines, packaging machines, etc. Service objects: integrators, intermediaries, etc.

Service purpose: We will effectively solve the packaging problems for customers, recommend suitable product types according to the cargo size and factory requirements provided by customers, and provide personalized product packaging and transportation plans according to customer needs.

Company Products

Turntable Wrapping Machine 【with Inclined Plane/with Weighing/with Press Top】 M-type Wra Machine, Explosion-proof Wrapping Machine, Stainless Steel Wrapping Machine Rotary Support Wrapping Machine, Automatic Film Feed/Cut-off Wpping Machine Secondary Wrapping Machine, Luggage Wrapping Machine, Small Parts Wrapping Machine Top Wrapping Machine, M-type Top Wra Machine Self-propelled Wrapping Machine 【Charging Type/Machine Can Be Moved】 Single Arm Wrapping Machine, Cantilever Wrapping, etc.

PART 01

Disc-type winding machine



PART 01

Self-propelled winding machine



Part 2 Disc-shaped

Standard winding machine

Winding machine technical parameters

Disc load bearing	≤2000Kg
Disc diameter	1500mm 【Other sizes be customized】
Winding height	2000mm 【Other sizes can be customized】
Disc height above the ground	78mm
Disc	0-13 revolutions/min
Machine weight	500kg
Power supply	AC220V/50HZ 【2phase electricity】
Machine size	1500*2500*2400mm 【Actual size to be determined according to the size of the】



Configuration list

Frequency converter	Risda
PLC	Risda
Text	Risda
Photoelectricity	Omron
Motor	Mingji
Limit switch	Zhengtai
Proximity switch	Zhengtai
The above configuration is subject to continuous product updates	Not separately notify

Part 2 Disc type 【plus weighing】



Non-standard winding machine 【with weighing】

Winding machine technical parameters

Disc load bearing	≤2000Kg
Disc diameter	1500mm 【Other sizes be customized】
Winding height	2000mm 【Other sizes can be customized】
Disc height above the ground	78mm
Disc	0-13 revolutions/min
Machine weight	500kg
Power supply	AC220V/50HZ 【 2phase electricity】
Machine size	1500*2500*2400mm 【Actual size to be determined according to the size of the】



Configuration list

Frequency converter	Risda
PLC	Risda
Text	Risda
Photoelectricity	Omron
Motor	Mingji
Limit switch	Zhengtai
Proximity switch	Zhengtai
The above configuration is subject to continuous product updates	Not separately notify

Part 2 Disc-type 【pressure cap】

Non-standard winding machine 【light goods bubble goods pressure top/hand truck loading plus ramp】

Pressure top/inclined slope winding machine technical parameters

Disc load bearing	≤2000Kg
Disc diameter	1500mm 【Other sizes be customized】
Winding height	2000mm 【Other sizes can be customized】
Disc height above the ground	78mm
Disc	0-13 revolutions/min
Machine weight	500kg
Power supply	AC220V/50HZ 【2phase electricity】
Machine size	1500*2500*2400mm 【Actual size to be determined according to the size of the】



Configuration list

Frequency converter	Risda
PLC	Risda
Text	Risda
Photoelectricity	Omron
Motor	Mingji
Limit switch	Zhengtai
Proximity switch	Zhengtai
The above configuration is subject to continuous product updates	Not separately notify

Part 2 Automatic film loading/breaking



Non-standard winding machine 【automatic film loading/automatic film breaking】 (air source required)

Automatic coating/breaking film winding machine technical parameters

Disc load bearing	≤2000Kg
Disc diameter	1500mm 【Other sizes be customized】
Winding height	2000mm 【Other sizes can be customized】
Disc height above the ground	78mm
Disc	0-13 revolutions/min
Machine weight	500kg
Power supply	AC220V/50HZ 【 2phase electricity】
Machine size	1500*2500*2400mm 【Actual size to be determined according to the size of the】



Configuration list

Frequency converter	Risda
PLC	Risda
Text	Risda
Photoelectricity	Omron
Motor	Mingji
Limit switch	Zhengtai
Proximity switch	Zhengtai

The above configuration is subject to continuous product updates

Not separately notify

Part 2 M-shaped; M-type

Non-standard winding machine [M type] handcart for loading and unloading / chuanzi pallet

M-type winding machine technical parameters

Disc load bearing	≤800Kg
Disc diameter	1650mm 【Other sizes be customized】
Winding height	2000mm 【Other sizes can be customized】
Disc height above the ground	78mm
Disc	0-13 revolutions/min
Machine weight	500kg
Power supply	AC220V/50HZ 【 2phase electricity】
Machine size	1650*2500*2400mm 【Actual size to be determined according to the size of the】



Configuration list

Frequency converter	Risda
PLC	Risda
Text	Risda
Photoelectricity	Omron
Motor	Mingji
Limit switch	Zhengtai
Proximity switch	Zhengtai

The above configuration is subject to continuous product updates

Not separately notify

Part 2 explosion-proof

Non-standard winding machine 【explosion-proof】 (for chemical plants)

Explosion-proof winding machine technical parameters

Disc load bearing	≤2000Kg
Disc diameter	1500mm 【Other sizes be customized】
Winding height	2000mm 【Other sizes can be customized】
Disc height above the ground	78mm
Disc	0-13 revolutions/min
Machine weight	500kg
Power supply	AC220V/50HZ 【 2phase electricity】
Machine size	1500*2500*2400mm 【Actual size to be determined according to the size of the】



Configuration list

Frequency converter	silin
PLC	xinjie
Text	xinjie
Photoelectricity	Omron
Motor	Kende
Limit switch	Zhengtai
Proximity switch	Zhengtai
The above configuration is subject to continuous product updates	Not separately notify

Part 2 Stainless steel disc type

Non-standard winding machine 【stainless steel body】

Stainless steel winding machine technical parameters

Disc load bearing	≤2000Kg
Disc diameter	1500mm 【Other sizes be customized】
Winding height	2000mm 【Other sizes can be customized】
Disc height above the ground	78mm
Disc	0-13 revolutions/min
Machine weight	500kg
Power supply	AC220V/50HZ 【 2phase electricity 】
Machine size	1500*2500*2400mm 【Actual size to be determined according to the size of the】



Configuration list

Frequency converter	Risda
PLC	Risda
Text	Risda
Photoelectricity	Omron
Motor	Mingji
Limit switch	Zhengtai
Proximity switch	Zhengtai
The above configuration is subject to continuous product updates	Not separately notify

Part 2 Rotary support 【Super load-bearing 4 tons】



Non-standard winding machine [rotary support] suitable for super heavy cargo of 4 tons

Rotary support; Winding machine technical parameters

Disc load bearing	≤4000Kg
Disc diameter	1500mm 【Other sizes be customized】
Winding height	2000mm 【Other sizes can be customized】
Disc height above the ground	78mm
Disc	0-13 revolutions/min
Machine weight	600kg
Power supply	AC220V/50HZ 【2phase electricity】
Machine size	1500*2500*2400mm 【Actual size to be determined according to the size of the】



Configuration list

Frequency converter	Risda
PLC	Risda
Text	Risda
Photoelectricity	Omron
Motor	Mingji
Limit switch	Zhengtai
Proximity switch	Zhengtai

The above configuration is subject to continuous product updates

Not separately notify

Part 2 Cantilever

Non-standard winding machine [cantilever] suitable for large goods/overweight products

Overhanging Winder Technical Parameters

Goods of unlimited weight	Goods placed on the middle machine rotating
Machine width	2000mm 【Other sizes can be customized】
Machine length	3000mm 【Other sizes can be customized】
Wrapping starting point	10mm
Turntable speed	0-13 rev/min
Total machine weight	500kg
Power	AC220V/50HZ 2-pole electricity】
Machine size	2000*3000*3500mm 【Actual size to be determined according to the size of the goods】



Configuration list

Frequency converter	Risda
PLC	Risda
Text	Risda
Photoelectricity	Omron
Motor	Mingji
Limit switch	Zhengtai
Proximity switch	Zhengtai
The above configuration is subject to continuous product updates	Not separately notify

Part 2 Single cantilever

Non-standard winding machine [single cantilever] suitable for large goods/overweight products

Overhanging Winder Technical Parameters

Goods of unlimited weight	Goods placed on the middle machine rotating
Machine width	2000mm 【Other sizes can be customized】
Machine length	3000mm 【Other sizes can be customized】
Wrapping starting point	10mm
Turntable speed	0-13 rev/min
Total machine weight	500kg
Power	AC220V/50HZ 2-pole electricity】
Machine size	2000*3000*3500mm 【Actual size to be determined according to the size of the goods】



Configuration list

Frequency converter	Risda
PLC	Risda
Text	Risda
Photoelectricity	Omron
Motor	Mingji
Limit switch	Zhengtai
Proximity switch	Zhengtai
The above configuration is subject to continuous product updates	Not separately notify

Part 2 Two-dimensional plane; 2D plane



Non-standard winding machine [2D] suitable for the overall packaging of round goods

Secondary dimensional winding machine technical parameters

Disc load bearing	≤2000Kg
Disc diameter	1500mm 【Other sizes be customized】
Winding height	2000mm 【Other sizes can be customized】
Disc height above the ground	78mm
Disc	0-13 revolutions/min
Machine weight	500kg
Power supply	AC220V/50HZ 【2phase electricity】
Machine size	1500*2500*2400mm 【Actual size to be determined according to the size of the】



Configuration list

Frequency converter	Risda
PLC	Risda
Text	Risda
Photoelectricity	Omron
Motor	Mingji
Limit switch	Zhengtai
Proximity switch	Zhengtai
The above configuration is subject to continuous product updates	
Not separately notify	

Part 2 roller type

Non-standard roller winding machine 【online】 Suitable for assembly line equipment

Roller type winding machine technical parameters

Disc load bearing	≤2000Kg
Disc diameter	1500mm 【Other sizes be customized】
Winding height	2000mm 【Other sizes can be customized】
Disc height above the ground	400mm
Disc	0-13 revolutions/min
Machine weight	500kg
Power supply	AC220V/50HZ 【 2phase electricity】
Machine size	1500*2500*2400mm 【Actual size to be determined according to the size of the】



Configuration list

Frequency converter	Shilin
PLC	huichuan
Touch screen	tontai
Photoelectricity	Omron
Motor	Mingji
Limit switch	Zhengtai
Proximity switch	Zhengtai

The above configuration is subject to continuous product updates

Not separately notify

Part 2 chain-type

Non-standard chain winding machine 【online】 Suitable for assembly line equipment

Roller type winding machine technical parameters

Disc load bearing	≤2000Kg
Disc diameter	1500mm 【Other sizes be customized】
Winding height	2000mm 【Other sizes can be customized】
Disc height above the ground	400mm
Disc	0-13 revolutions/min
Machine weight	500kg
Power supply	AC220V/50HZ 【 2phase electricity 】
Machine size	1500*2500*2400mm 【Actual size to be determined according to the size of the】



Configuration list

Frequency converter	Shilin
PLC	huichuan
Touch screen	tontai
Photoelectricity	Omron
Motor	Mingji
Limit switch	Zhengtai
Proximity switch	Zhengtai
The above configuration is subject to continuous product updates	Not separately notify

Part 2 Self-propelled 【rechargeable】



Self-propelled strapping machine 【Unlimited large goods size/weight】 Rechargeable

Self-propelled winding machine technical parameters

Unlimited size/weight	As long as the ground is flat/minimum cargo size 70*70cm unlimited large
Operation time	6/one charge
Column winding height	There are 4 models: 1.7m/2m/2.4m/2.8m [you can one height]
Winding start point	10mm
Travel speed	80m/minute
Battery capacity	105AH
Power	AC220V/50HZ [2-phase electricity]
Machine size	1700*700*2400mm [according to the selected column height]



Configuration list

Touch screen	Risda
Photoelectricity	Risda
Controller	Risda
Motor	Bomai
Limit switch	Zhengtai
Battery	Chao Wei
The above configuration is subject to continuous product updates	Not separately notify

Part 2 Baggage carousel

Conveyor/pallet wrapping machine

Conveyor belt machine technical parameters

Rotating disk load capacity	≤100Kg
Minimum specifications	200*240*300mm
Maximum specifications	500*500*450mm
Power	0.8kw
Rot disk speed	0-35 revolutions per minute
Weight of the whole machine	180kg
Power supply	AC220V/50Z 【 2-phase electricity 】
Machine size	1650*600*1900mm 【The actual size is determined according the size of the goods】



Configuration list

Frequency converter	Risda
PLC	Risda
Text	Risda
Photoelectricity	Omron
Motor	Mingji
Limit switch	Zhengtai
Proximity switch	Zhengtai
The above configuration is subject to continuous product updates	Not separately notify

Part 2 Baggage carousel

Conveyor/pallet wrapping machine

Conveyor belt machine technical parameters

Rotating disk load capacity	≤100Kg
Minimum specifications	200*240*300mm
Maximum specifications	1100*470*900mm
Power	0.8kw
Rot disk speed	0-35 revolutions per minute
Weight of the whole machine	240kg
Power supply	AC220V/50Z 【 2-phase electricity 】
Machine size	1650*600*1900mm 【The actual size is determined according the size of the goods】



Configuration list

Frequency converter	Risda
PLC	Risda
Text	Risda
Photoelectricity	Omron
Motor	Mingji
Limit switch	Zhengtai
Proximity switch	Zhengtai
The above configuration is subject to continuous product updates	Not separately notify

Part 2 Little machine

Small cargo strapping film machine

Small machine; Winder technical parameters

Rotating disk load capacity	≤100Kg
Minimum specifications	300*400*400mm
Maximum specifications	600*600*1200mm
Power	0.8kw
Rot disk speed	0-35 revolutions per minute
Weight of the whole machine	240kg
Power supply	AC220V/50Z 【 2-phase electricity 】
Machine size	1500*550*1940mmThe actual size is determined according the size of the goods】



Configuration list

Frequency converter	Risda
PLC	Risda
Text	Risda
Photoelectricity	Omron
Motor	Mingji
Limit switch	Zhengtai
Proximity switch	Zhengtai
The above configuration is subject to continuous product updates	Not separately notify

PART 0?

Customer use case

Part 3 Customer use case



Part 3 Customer use case





Thank you all

commit to development

Cooperation and mutual
encouragement



Factory address: No.158, Shenzhang Road, Xinzhuang Town, Changshu City, Jiangsu Province

Phone/WeChat: 1370157188 13915666777